






ULTRA GRIP 1000

ULTRA GRIP 1000 is a professional high density floor underlay made of 100% organic materials.
Cardboard box - 40 rolls



	Material	Polyurethane (1000 kg/m³)	Norm
	RWS Sound proofing	7 %	EPLF WD 021029-5
	IS Sound dampening	16 dB	DIN EN 10140
	R Heat conductivity	0,010 m²K/W	EN 12664
	SD Moisture protection	-	DIN EN 12086
	CS Pressure proofing	450 kPa	DIN EN 826
	CC Pressure resistance	-	DIN EN 1606
	DL Permanent elasticity	>3 000 000	DIN EN 13793
	RLB Shock resistance	800 mm	DIN EN 13329
	PC Floor leveling	0,79 mm	CEN TS 16354
	RTF Fire resistance	Bfl	DIN EN13501-1

Uses:

Floor underlay with soundproofing properties, with high load resistance. Dedicated to floating floors with click system. Does not require the use of a vapor barrier film.

Properties:

Effective sound absorption, water resistance, moisture protection. Free of plasticizers, asbestos, formaldehydes, halogens and heavy metals. Complies with A+ VOC emission guidelines, Blue Angel economic certification and German AgBB program Water, most household cleaners, salt solutions, acids, bases, partially resistant to organic solvents and hydrocarbons.

Chemical resistance:

Store indoors, protect from sunlight.

Storage:

Easy cutting with wallpaper cutter. Arrange with the adhesive layer upwards (the side protected by a protective film).

Installation:

Join the underlayment strips using floor underlayment tape - such as Korner's dedicated multifunctional aluminum tape.