

Partition Wall 580x2750x65



Technical Card

1. Material:
MDF
2. Coating:
pre-impregnation film
3. Bonding:
hot melt adhesive
4. Application/functionality:
decoration of residential interiors and public use rooms; room division/separation of zones within a room.
5. Technical parameters:
 - tolerance of lamella length [mm]
 - tolerances for lamella thickness [mm]
 - tolerances for lamella width [mm]
 - wall weight [kg]
 - density of the board used to manufacture the laths:
 - cut: at an angle of 90°
 - thermal resistance of the product:
6. Installation method:
According to the Installation Instructions.
7. Storage:
protect from direct weathering, moisture; store in dry and closed rooms in a horizontal position (in living conditions), away from heat sources; store at a temperature of up to 50°C, with humidity max. 60%
8. Recommendations:
do not use chemicals to clean stains; use the product only indoors, protect from moisture and temperatures above 50°C.
9. Additional information:
MDF has hygroscopic properties, which may result in the expansion of the material under the influence of moisture; mate-material is susceptible to stresses that cause deviations in straightness; these natural characteristics of the material cannot be considered as product defects; formaldehyde emission: Class E05, E1

+0/-2
+0.5/-0
+0.5/-0
23
600-800 kg/m³
w tolerancji ±1°
max 50°C

The products covered by this Technical Data Sheet comply with the European REACH Regulation No. 1907/2006 and do not contain substances listed on the SVHC Candidate List (substances of very high concern). Space walls are not construction products and are not subject to Directive 305/2011.